



CONNECTIONS

CL	Tractor side	Control Line	M22x1.5 DIN 3852-1X
SL		Supplementary Line	M22x1.5 DIN 3852-1X
RL		Return line	M18x1.5 ISO 6149
CT	Trailer side	Control Line	M22x1.5 DIN 3852-1X
ST		Supplementary Line	M22x1.5 DIN 3852-1X
VH		Vent hole/filling plug	***
DP		Drain plug	***

LIMITS OF USE

Max pressure CL port	160 bar
Max pressure SL port	50 bar
Hydraulic fluid	Hydraulic oil DIN 51524
Viscosity range	10/380 cSt
Filtering level	NAS 1638 CLASS 9
Temperature	-20/+90 °C

ORDER PART NUMBER

20 6613

6613: Management device for SAHR spring cylinders

20: Product class

Key features and operating instructions:

- The device has no function while the vehicle is in motion:
-CL and CT lines connected
-SL and ST lines connected
- Piston-latch for the ST line isolation and hand pump for the manual release of ST line of SAHR cylinder and for the emergency movement even in case the tractor is unhooked
- Automatic reactivation of the piston-latch in case of pressure increase on the SL line
- Mechanical safety displays suggesting the eventual detachment of the emergency and/or parking brake
- Reservoir for the manual unlocking of the SAHR cylinder and for the oil containment in event the pressurized dual line coupling SL accidentally detaches
- Manual device for CL line depressurization

